

2.5/2.5系列选型规则/Group 2.5/2.5 Ordering Code Rules

B	H	P	2.5/2.5	A1	D	10/10	C0	Z0/Z0	E	省略/omit	省略/omit
博顿 Boden	材质 Material	功能 Function	系列 Group	前盖 Front cover	旋向 Rotation	排量 Displacement	轴伸 Shaft	泵体油口 Ports	特殊结构 Special structure	可选项 Options	其他 Other
A	前、后盖材料为铝合金 Front and end cover material aluminum	P 泵 Pump	2.5系列 Group 2.5 / 2.5 + 2.5系列 Group 2.5	见2.5系列目录 Ref. Group 2.5 catalogue	D 顺时针转 Clockwise S 逆时针转 Counter clockwise	PA PB 10 10 12.5 12.5 14 14 16 16 18 18 19 19 20 20 23 23 25 25 26.5 26.5 28 28 30 30 32 32 36 36 40 40	见2.5系列目录 Ref. Group 2.5 catalogue	见2.5系列目录 Ref. Group 2.5 catalogue	E 不通油型 Separated type		特殊设计 special designing
H	前、后盖材料为铸铁，压力比铝盖高 30bar。 Front and end cover material cast iron, pressure 30 bar higher than aluminum covers										
可选项 Options											
	省略-温度范围在-10℃~+80℃, 进油口最高绝对压力为3bar。 Omit-Range between -10℃ and +80℃, inlet pressure up to max. 3 bar absolute.										
V	适用于高温介质，温度范围在-10℃~+120℃。 Version suitable for fluid at hi-temperatures, range between -10℃ and +120℃.										
H	适用于低温介质，温度范围在-40℃~+80℃。 Version suitable for fluid at low-temperatures, range between -40℃ and +80℃.										
N	适用于进油口最大绝对压力3~10bar。 Version suitable for inlet pressure up to max. 3 and 10 bar absolute.										
如需其它特殊选项请联系本公司工程师 For other special options, please contact our engineers.											

如需其它型号请见详情页或联系本公司工程师

If you need other models, please see the details page or contact our engineers.